



Heat Pipe

Features

- · A conversion of the density of heat flux
- · Fast heat balancing
- · Passive components
- · Light weighted

Applications

Applicable industries from small to large scale of products

Electronic Components - 5G, Aerospace, AI, AIoT, AR/VR/MR/XR, Automotive, Consumer Devices, Datacom, Electric Vehicle, Electronic Products, Energy Storage, Industrial, Lighting Equipment, Medical, Military, Netcom, Panel, Power Electronics, Robot, Servers, Smart Home, Telecom, etc.

Properties

General Specifications

- · Length: 100~350mm
- · Flattening thickness: half of the diameter 1/2Ø

e.x. Ø6 = 3mm

 \cdot Bending angle R: 3 times of the diameter

>3*Ø

e.x. Ø6 =18mm

· Bending angle : more than 120 degrees

Mechanism		
	liquid	1
ste	am liquid	condensation
	capillary structure	zone
evaporation	SHOCIOIE	

Diameter(mm)	Thickness(mm)	Width(mm)
Ø4	2	5.65
	2.5	5.55
	3	5.45
Ø5	2	6.91
	2.5	6.59
	3	6.32
	3.5	6.01
	4	5.68
Ø6	2	8.50
	2.5	8.18
	3	7.95
	3.5	7.65
	4	7.39
Ø8	2	11.65
	2.5	11.39
	3	11.15
	3.5	10.83
	4	10.60
	4.5	10.27
	5	10.01
	6	9.36

- · Thickness Tolerance:+0.05/-0.10 mm
- · Width Tolerance:+0.15/-0.20 mm

Customizable per customer's requirement.

T-Global Techonology Co., Ltd.

No.33, Ln.50, Daren Rd., Taoyuan Dist., Taoyuan City 330058, Taiwan

T +886-3-361-8899

E service@tglobalcorp.com

W www.tglobalcorp.com



Version20

20250124







NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film and release paper do not affect the function of the product. If there is no special requirement, the default depends on the product of the product of potential use are beyond our control, all recommendations or suggestions are presented with our guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to material or its use.