



# Thermoelectric Cooling Chip

## Features

- Small bulk and light weight
- No vibration and noise-free
- Precise temperature control
- High reliability

## Applications

### Rugged environment durable

It's widely used in medical equipment, freezer, drinking fountains, military petroleum instruments as these applications need thermal cycling control. Besides, it's also widely being applied to control the temperature during fabrication of semiconductor.

## Properties

Size(mm)	Height(mm)	Imax(A)	Vmax(V)	Watt(W)	Qmax(W) @27°C	Qmax(W) @50°C	R(Ohm)
15×15	3.1	6.0	3.8	22.8	13	14.3	0.45±10%
	3.4	8.5	2.1	17.9	10.3	11.3	0.20±10%
	3.6	3.9	3.8	14.8	8.6	9.5	0.85±10%
	3.8	3.0	3.8	11.4	7.3	8	1.00±10%
	3.9	6.0	2.1	12.6	7.4	8.2	0.30±10%
	4.7	2.0	3.8	7.6	4.4	5	1.65±10%
20×20	3.1	6.0	8.8	52.8	29.7	32.7	1.05±10%
	3.4	8.5	3.8	32.3	18.8	20.8	0.35±10%
	3.6	3.9	8.8	34.3	18.7	20.9	1.95±10%
	3.8	3.0	8.8	26.4	16.6	18	2.20±10%
	3.9	6.0	3.8	22.8	13.6	14.9	0.55±10%
	4.7	2.0	8.8	17.6	10.2	11.2	3.70±10%
30×30	3.15	6.0	15.7	94.2	53.1	59.1	1.90±10%
	3.45	8.5	8.8	74.8	43.1	48	0.85±10%
	3.65	3.9	15.7	61.2	35.2	39	3.50±10%
	3.85	3.0	15.7	47.1	29.8	32.5	4.00±10%
	3.95	6.0	8.8	52.8	31.1	34.2	1.25±10%
	3.95	6.0	11.8	70.8	48	52.8	1.65±10%
	4.75	2.0	15.7	31.4	18.2	19.5	6.70±10%
40×40	3.45	8.5	15.7	133.5	77.1	85	1.50±10%
	3.95	6.0	15.7	94.2	55.6	61	2.20±10%

► For special sizes, please contact our product consultants.

## T-Global Technolgy Co., Ltd.

No.33, Ln.50, Daren Rd., Taoyuan Dist., Taoyuan City 330058, Taiwan

T +886-3-361-8899 E service@tglobalcorp.com W www.tglobalcorp.com

Version20  
20250124



NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film and release paper do not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented with out guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.